


KEYNOTES

- PARTITION TO PROVIDE ACCESS TO SERVICES BEHIND. REMOVEABLE PANELS, SLIDING DOORS OR SIMILAR. SIZE OF SPACE TO BE BASED ON HVAC EQUIP. NEEDED.
- (2) 50 x 50 MM CERAMIC TILE AND CERAMIC BASE.
- 3 CUSTOM BOOKCASES AND CABINET. SEE MILLWORK. MEASURE ON SITE.
- 4 FINISHED FLOORS TO BE SEALED AND POLISHED CONCRETE.
- 5 GLAZED PARTITION. SEE DETAILS.
- (6) CONCRETE STAIRS POURED ON EXPOSED ROCK AS NEEDED.
- (7) GYPSUM BULKHEAD ABOVE. PAINT TO MATCH KITCHEN.
- (8) KITCHEN CUPBOARDS ABOVE.
- (9) STAINLESS STEEL DOUBLE SINK.
- (10) STANDARD SIZE FRIDGE. PROVIDE ELEC. DUTLET ON BACK WALL.
- (11) STANDARD SIZE ELEC. STOVE. PROVIDE OUTLET AS NEEDED.
- (12) DOOR FRAME SHOULD BE FLUSH WITH INSIDE OF WALL.

- (13) LINE OF ROOF OVERHANG ABOVE.
- (14) LINE OF CANOPY SHELTER ABOVE SEE DETAILS

WALL TYPES

WT1 - 12.7MM GYPSUM, 38×140 WOOD STUDS, AIR/VAPOR BARRIER, GLASS FIBRE INSULATION, 7.5MM PLYWOOD OR OSB SHEATHING, METAL SIDING



Ν